

## IN THE CLAIM

Please cancel Claim 1, without prejudice or disclaimer of the subject matter thereof, and add new claim 2 as the following. The added new claim 2 is based on the original claim 1 and the features in Figs. 1 - 3 of the present invention. Thereby, it is assured that the new claims are based on the original claim and specification and thus no new matter is added. The relation of the new claim with respect to the original claim are shown in the following REMARK, Examiners can read the claims more easily from the REMARK.

## **LIST OF CLAIMS:**

Claim 1. (Cancelled)

Claim 2. (New) An adjustable spanner comprising:  
a holding portion installed at one end of the spanner body;  
a retaining jaw installed at another end of the spanner body;  
a movable jaw installed to the retaining jaw; the movable jaw being  
slidable along a slide track at a head portion of the spanner body; and the  
lower side of the movable jaw having a plane;  
a neck portion extended from the plane of the movable jaw; and  
a round cylinder engaging portion extended from a lower side of the  
neck portion;  
wherein two sides of the upper end of the slide track are formed with  
respective auxiliary projecting track; two sides of a lower edge of the  
movable jaw are formed with respective inclined planes; the inclined  
planes are reduced toward the neck portion so as to enhance the strength of  
the structure; the inclined planes are configured to be matchable to the two  
auxiliary projecting tracks; each auxiliary projecting track is extended

from a respective upper surface of the slide track with an angle between 60 to 85 degrees so as to enhance the strength of the adjustable spanner; and

wherein the movable jaw, the neck portion and round cylinder engaging portion are integrally formed.